



12-Bay Storage Server, Xeon Silver 4110, 16GB RAM, RAID, 250GB SSD, WINPRO10



ICT TYPE 1

Key Features

- 2 x Intel® Xeon® processor Scalable v1/v2 product family (LGA 3647 Socket P0)
- 2 x 10/100/1000Base-T Gigabit Ethernet RJ-45 Port with Link Aggregation and IPv4/IPv6 support
- ASWM Enterprise Software for Web-based Monitoring and System Alarm notifications
- On-board ASMB9-iKVM for KVM-over-IP Remote Management
- 1+1 Hot-Swappable Redundant Power Supply
- Designed for High Availability Cluster Video Storage Server System deployment
- Premium components with Ultimate Durability Solid Capacitor for premium efficiency

Technical Specification

SYSTEM	
Recommended Operating System	<ul style="list-style-type: none">• Windows® Server 2012 R2 / 2012 / 2008 R2 (Hyper-V supported)• RedHat® Enterprise Linux• SuSE® Linux Enterprise Server• CentOS• Ubuntu• vmware• Citrix XenServer
Processor	1 x Intel® Xeon® Processor Scalable Silver-4110 (2.10GHz Base, 3.00GHz Turbo, 8 Core, 11.00M)
System Memory	1 x 16GB ECC DDR4 2666 Memory, Expandable to 4096GB
Video Controller	Integrated Video Controller

Rear I/O Port	<ul style="list-style-type: none"> • 2 x USB 3.0 • 2 x 10/100/1000Base-T Gigabit Ethernet RJ-45 Port • 1 x IPMI RJ-45 Port • Serial Port (DB-9) • VGA (D-Sub) • Q-Code/Port 80 LED indicator
Expansion Slot	<ul style="list-style-type: none"> • 2 x PCI-E Gen3 x16 (x16 link) LP, HL • 4 x PCI-E Gen3 x8 (x8 link) LP, HL • 1 x OCP Mezzanine (Gen3 x16 link)
Front Panel	<ul style="list-style-type: none"> • 2 x USB 3.0 • 1 x VGA • Power Switch and LED indicator • Location Switch and LED indicator • Reset Switch • HDD Activity LED indicator • Message LED indicator • LAN 1-2 LED indicator
Storage Disk Drive	<ul style="list-style-type: none"> • 12 x 2.5" or 3.5" 12Gb SAS/ Hot-Swap Slot • 2 x 2.5" Rear Hot-Swap Slot • 2 x M.2 (2280, 2260, 2242)
RAID	RAID 0, 1, 5, 6, 10, 50, 60 Supported
Power Supply	800W Hot-Swappable Redundant PSU 1+1, 80 Plus Platinum, 110~240 VAC
MECHANICAL	
Material	Heavy-Duty Pre-Plated SPGC Cold-Rolled Steel Chassis
Cooling	4 x Redundant Hot Swappable Chassis Fans
Dimension	615 mm x 444 mm x 88 mm (W x D x H)
Weight	25 kg
Mounting	2U 19" Rack Mount
ENVIRONMENTAL	
Operating Temperature	-10°C to 50°C
Storage Temperature	-20°C to 60°C
Relative Humidity	10% to 80% non-condensing
REGULATORY APPROVALS	
Standards	<ul style="list-style-type: none"> • CE • FCC • BSMI • C-Tick • Manufactured in ISO9001:2015 and ISO14001:2015 Certified Facility

สนใจสอบถามผลิตภัณฑ์และโซลูชันได้ที่ บริษัท ทีโซลูชันส์ จำกัด โทร. 02-570-0444
ID Line :@tsolutions